



Impact Dot matrix Printer

- Support GB18030
- Three-ply capable
- Black mark orientation
- Bi-directional printing



DP-3046

www.appostar.com

Tel: +886-2-2910-6168 ext: 251

Email: sales@appostar.com

Specification

Model Name

DP-3046

Printing method	9-Pin serial impact dot-matrix printing
Printing width	63.5 mm
Column capacity	400 dots/line
Printing speed	4.5 line/s
Interface	USB / Lan
Printing paper	75.5±0.5mm x Φ 80mm(max)
Line spacing	4.23mm (Adjustable by commands)
Character size	ANK, Font A: 1.6x3.1mm (9x9 dots) Font B: 1.2x3.1mm (7x9 dots) Chinese, traditional Chinese: 2.7x2.7mm (16x16 dots)
Column number	76mm paper: Font A - 32 columns /Font B - 42 columns / Chinese, traditional Chinese -16 columns

Character

Extension character sheet	PC437(Standard Europe)/ Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe/ Greek / Hebrew/ East Europe/ Iran/WPC 1252 / PC866(Cyrillic#2) / PC852(Latin 2) / PC858 / IranII / Latvian / Arabic/ PT151(1251)
---------------------------	--

Power

Power adaptor	Input: AC 110V/220V, 50 ~ 60Hz
Power source	Output: DC 24V/2.5A
Cash drawer output	DC 24V/1A

Cutter

Auto cutter	Partial
-------------	---------

Physical characteristics

Weight	1.28KG
Dimensions	220x150x140mm (DxWxH)

Environmental Requirements

Work environment	0~45°C, 10~80% RH
Storage environment	-10 ~60°C, 10~90% RH (no condensation)

Reliability

Printer head life / Cutter life	10 Million Lines / 1 Million cuts
---------------------------------	-----------------------------------

• Product specification is subject to change without prior notice.

Application and location:

Restaurant and shops

Government organizations

ERP processor

Warehouse management

