



KI Series

KI-100



Specification

Model Name	KI-100
CPU	RK3128 Quad core 1.2Ghz
Main Memory	1GB / 2GB (Optional)
Internal memory	8GB / 16GB (Optional)
Display	10." LCD IPS panel
Resolution	1280 x 800
Luminance	500 cd/m2
Network/Interface	
LTE Cat4 WiFi router	FDD:1,3,7,8,20,28 / TDD:38,40,41 / WCDMA:B1,B3,B5,B8 / GMS: 850/900/1800/1900 MH
Ethernet	10M/100M
Bluetooth	4.0
Card Slot	SD Card (MAX 32G)
USB	1 x MicroUSB / 2 x USB
System	
Android	7.1.2
Powering	
Power support	AC Power / Battery input
Other	
EasyCard Reader	Included
Thermal Printer	2 inch
Speaker	1.5W x2
Environment	
Security Locks	Included
Operating Temperature	5°C ~ 50°C
Storage Temperature	-20°C ~ 50°C
Operating Humidity	10%~80% RH
Storage Humidity	20% ~90% RH
Mechanical	
Housing Color	Sliver
Demension	W380 x D210 x H1449.92mm
Weight	36 KG

• Product specification is subject to change without prior notice.

POS Accessories



Customer display



POS System



RTP-3280(3")



RTP-2264(2")



Scanner



Cash Drawer

Authorized Distributor/Reseller

Appostar



3F., No. 18, Ln. 42, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan (R.O.C.)

Tel: 886-2-2910-6168 Fax: 886-2-89147553 Email: sales@appostar.com