

Appostar

RTP Series

RTP-3262



www.appostar.com

Tel:+886-2-2910-6168 ext:251

Email:sales@appostar.com

RTP-3262

Specification

Printing	
Printing method	Direct thermal
Paper width	58 / 80 / 83 ± 0.5mm
Print width	48 ~ 80 ± 0.5mm
Paper roll diameter	Min:13mm Max:83mm
Column capacity	567 dots/line (Adjustable by commands)
Printing speed	300mm/s
Interface	USB+Serial+Lan / USB+Serial+Lan+Bluetooth / USB+Serial+Lan+WiFi
Line space	3.75mm(Adjustable by commands)
Column number	80mm paper: Font A - 42 columns or 48 columns/Font B - 56 columns or 64 columns/ Chinese, traditional Chinese - 21 columns or 24 columns
Character size	ANK, Font A: 1.5x3.0mm(12x24 dots) Font B: 1.1x2.1mm(9x17 dots) Chinese, traditional Chinese:3.0x3.0mm(24x24 dots)
Cutter	
Auto cutter	Partial
Barcode Character	
Extension character sheet	PC347(Standard Europe) / Katakana / PC850(Multilingual) / PC860(Portuguese) / PC863(Canadian-French) / PC865(Nordic) / West Europe / Greek / Hebrew / East Europe / Iran / WPC1252 / PC866(Cyrillic#2) / PC852(Latin2) / PC858 / Iranll / Latvian / Arabic / PT151(1251)
Barcode types	UPC-A / UPC-E / JAN13(EAN13) / JAN8(EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128
2D Barcode	QR CODE / PDF417
Input buffer	2048 Kbytes
NV Flash	256 Kbytes
Power	
Power adaptor	Input: AC 220V, 50~60Hz
Power source	Output: DC 24V / 2.5A
Cash drawer output	DC 24V / 1A
Physical characteristics	
Weight	1.1KG
Dimensions	140 x 130 x 133 mm (DxWxH)
Environmental Requirements	
Work environment	Temperature (0~45°C) humidity (10~80%)
Storage environment	Temperature (-10~60°C) humidity (10~80%)
Reliability	
Cutter life	2million cuts
Printer head life	150Km
Software	
Emulation	ESC/POS
Driver	Windows / JPOS / Linux / Android / Mac
Utility	Windows & Linux test Utility
SDK	iOS, Android, Windows

• Product specification is subject to change without prior notice.