




## GP Series

# POS Terminal

The New! GP-series models are elegant and powerful all-in-one systems, designed for the toughest retail and hospitality environments. Its robust and compact system fits beautifully on any point of sale counter. Its modular design features ensures guaranteed high serviceability.



Easy storage maintenance design



VESA for wall-mount



Splash-resistant on frontal



MSR / SCR and i-Button optional



## Specification

<b>Model Name</b>	<b>GP-3473</b>
Main Board	ITX-H110
CPU	Intel Core i5-6200U
Chipset	Intel H110 Express Chipset
Memory	4GB DDR3 (Max 8GB)
Display	15" TFT-LCD with LED backlight (1024 x 768)
Touch Panel	P-CAP touch
HDD	2.5" SATA HDD 320GB
Expansion	2 x Mini PCI-E slot
OS Compatibility	Windows 7, Windows 8, Windows 10
<b>External I/O Interface</b>	
Serial Port	2 x External COM Ports with 5V/12V selectable
Cash Drawer Port	1 x RJ11 with DC 12V (Optional)
VGA Port	1 x HDMI, 1 x VGA (DB15)
Audio Port	1 x Line in, 1 x Line out
Ethernet Port	1 x RJ45 10M/100 M/1G Base-T
USB Port	2 x USB 2.0 Type A, 4 x USB 3.0 Type A (1 x USB 2.0 on Panel Side Optional)
Speaker	2 x Integrated 1W Speaker
DC output Jack	1 x 12V/2.5A DC Jack
<b>Optional Peripheral</b>	
Magnetic Card Reader	ISO 7811 option 1/2/3 track
Finger Print	512dpi x 8bit gray scale, Capture area: 14.6 x 18.1 mm
i-button	Dallas Key
Wireless LAN	802.11 b/g
Customer Display	VFD / LCD Customer Display
Second Display	8 inch / 10 inch / 12 inch / 15 inch TFT-LCD display/non-touch
<b>Control / Indicator</b>	
Power Button	1
<b>Powering</b>	
Power support	AC 100V~240V / 60W power adapter (Optional 90W Adapter)
<b>Environment</b>	
EMC & Safety	CE/FCC Class A
Operating Temperature	5°C ~ 40°C
Storage Temperature	-20°C ~ 60°C
Operating Humidity	15%~80% RH
Storage Humidity	20% ~90% RH
<b>Mechanical</b>	
Housing Color	Black
Construction	ABS + SECC
Dimension(WxDxH)	400 x 225 x 320 mm
Weight	N.W. 8.5 kg

• Product specification is subject to change without prior notice.

## POS Accessories



Authorized Distributor/Reseller

# Appostar

CE FCC Tested To Comply With FCC Standards FOR HOME OR OFFICE USE

RoHS Compliant

3F., No. 18, Ln. 42, Minquan Rd., Xindian Dist., New Taipei City 231, Taiwan  
 Tel: 886-2-2910-6168 Fax: 886-2-8914-7553  
 Email: sales@appostar.com