

# ApPostar

YOUR RELIABLE GLOBAL PARTNER

## Label Printer

### OS-2130D



### Features

- For low to medium volume printing demand
- 2.83-inch(72mm) printing width, direct thermal barcode printer
- 203 dpi print resolution and up to 4ips(102mm/s) printing speed
- 32-bit CPU and 4MB Flash; 8MB SDRAM memory standard
- Communication interfaces –Serial RS-232 (9 pin), USB(2.0), Cash Drawer, Ethernet(Optional) to fit in various systems
- Buzzer for error warning function
- Internal Real Time Clock
- Support Windows 7
- Tear off bar Built-in

**APPOSTAR Technology Co.,Ltd.**

3F., No.18, Ln.42, Minquan Rd., Xindian Dist.  
, New Taipei City 231, Taiwan (R.O.C.)

Tel: 886-2-2910-6168

Fax: 886-2-8914-7553

Email: sales@appostar.com

© 2013 APPOSTAR Technology Co., Ltd. All rights reserved.

<b>Model Name</b>	<b>OS-2130D</b>
<b>Printing Method</b>	Direct Thermal
<b>Printing resolution</b>	203 dpi (8 dots/mm)
<b>Printing Speed</b>	2~4ips (102mm/s)
<b>Printing Length</b>	Max. 100" (2540mm)
<b>Printing Width</b>	Max 2.83"
<b>Memory</b>	4MB Flash ROM(2MB user available), 8MB DRAM(6MB user available)
<b>CPU Type</b>	32 bit RISC microprocessor 100
<b>Sensors</b>	Reflective( Left side )
<b>Operation Interface</b>	Button( Feed ) x 1
<b>Communication</b>	RS-232, USB, Cash drawer
<b>Fonts</b>	Internal character sets standard 5 alpha-numeric fonts from 0.049"H ~ 0.23" H (1.25mm ~ 6.0mm) Internal fonts are expandable up to 24x244 direction 0 ~ 270 rotation Soft fonts and 2-byte Asian fonts are downloadable Ability to print any Windows True Type Font easily
<b>1D Barcodes</b>	Code 39 , Code 93 Interleaved 2of 5, EAN-8, EAN-13,UPC-A,UPC-E, Postnet, Codabar, Code 128 subset A/B/C, UCC/EAN-128, UCC/EAN-128 K-MART, UCC/EAN-128 , Random Weight, Plessey, HBIC, Telepen, FIM, UPC2, UPC5,GS1 DataBar
<b>2D Barcodes</b>	MaxiCode, PDF417, Data Matrix (ECC 200 only), QR code, Composite codes
<b>Emulation</b>	Data Max / Eltron
<b>Software - Label editing</b>	Windows Driver (XP / Vista / Win 7) , Label Design Software
<b>Media Type</b>	Roll-feed, die-cut, continuous, fan-fold, tags,ticket in thermal paper
<b>Media</b>	Max width 3.03" (77 mm) , Min width 1" (25.4 mm) Max length 100
<b>Power Source</b>	100V~240V,1.8A, 50~60
<b>Optional Items</b>	Cutter, Stacker, RTC Card
<b>Real Time Clock</b>	Buzzer build-in & internal real time clock
<b>Environment</b>	
<b>Operating Temperature</b>	40°F~100°F (4°C~38°C)
<b>Storage Temperature</b>	-4°F~122°F (-20°C~50°C)
<b>Operating Humidity</b>	10%~90% RH non-condensing
<b>Storage Humidity</b>	10%~90% RH non-condensing
<b>Mechanical</b>	
<b>Housing Color</b>	Black
<b>Dimension(WxDxH)</b>	134 x 228 x 163 mm
<b>Weight</b>	1.2 kgs

Product specification is subject to change without prior notice.

