



Customer Display

- Unique feature to simultaneously display both customer display message and Flash video clip.
- 7" diagonal screen with 800 x 480 native display resolution.
- Spill proof true-flat bezel-free front panel with high quality protective glass.
- Stylish full glossy surface throughout monitor's appearance.
- Fully seal no ventilation hole design.
- Easy cable management routing through the mounting stand.
- Tool-free adjustable pole base.
- VESA 75 x 75 wall mounting standard.
- Plug & Play USB interface.



Specification

Model Name	PCM-1207
Color	Black or White
Display Type	7" TFT LCD with LED backlight
Display Area	152.40mm (W)x 91.44mm (H) (6" x 3.6")
Cover Lens	Mitsubishi PMMA, Hardness > 5H (JIS D0202), T > 93%
Resolution	800 x 480
Brightness	250 cd / m ²
Contrast Ratio	1900/1/20 08:01:00 PM
Response Time	30 ms
LCD Viewing Angle	110 (H) / 160 (V) degrees
Rotation Angle	Vertical: 30 degree / Horizontal: 120 degree
I/O Interface	USB
Wall Mounting	Standard VESA, 75 x 75 mm
Power Supply	5V DC @0.5A max(via USB)
Power Consumption	2.5W
Agency Approvals	CE , FCC, BSMI
Media player Area	
Resolution	800 x 240
Background	Flash(.swf)
Customer Display	
Resolution	800 x 240
Character type	Alphanumeric and Compound (2-Bytes) Characters
Number of Characters	Alphanumeric : 30x4 / 30x2 / 20x2 Compound Words : 15x4 / 10x2
Background Color	Adjustable
Command	ESC / POS, AEDEX(20x2)
Font Size	Adjustable
Font Type	Adjustable, depend on OS
Language Support	Adjustable, depend on OS
Environment	
Operation Temperature	0°C to 40°C
Storage Temperature	-20°C to 60°C
Humidity	20% to 90% non-condensing
Physical Dimension	
Dimension (W x D x H)	181x153x203~253mm
Weight	1.1 kg (w/pole base)

• Product specification is subject to change without prior notice.



Authorized Distributor/Reseller

Appostar

